vG incorporated

AVAILABLE AS CUSTOM/LOGO MATTING

CHAMPION SUPER NOP

54 OZ INDOOR/OUTDOOR MATTING

Our most popular mat is timeless in any environment.

Dense and thoughtfully crafted, Champion Super Nop features warm neutrals, fashionable brights and classic standard colors. Made with 100% ASOTA® polypropylene fibers, this carpet is UV stable, stain resistant, durable and a highly resilient non-woven carpet. Champion Super Nop is our highest quality product that truly has something for everyone.

LET'S GET STARTED:
Contact your representative, call 1+ 866 284 6287 or email samples@vangelder-inc.com for samples and more information.

Bright Red 3014 (PMS 192 C)	Cardinal Red 3353* (PMS 7623 C)	Solid Crimson 3031 (PMS 484 C)	Burgundy 3035 (PMS 209 C)	Garnet 3138* (PMS 7645 C)	Pink 3091 (PMS 1905 C)
Orange 3018 (PMS 144 C)	Yellow 1025 (PMS 121 C)	Gold 1039 (PMS 7563 C)	Sky Blue 5149 (PMS 291 C)	Royal Blue 5182 (PMS 285 C)	Azure 5181* (PMS 540 C)
Steel Blue 5157* (PMS 534 C)	Midnight Blue 5154* (PMS 7546 C)	Prism 5155* (PMS 295 C)	Purple 3090 (PMS Med. Purple)	Turquoise 6096 (PMS 325 C)	Kelly Green 6042 (PMS 356 C)
Verde Green 6043* (PMS 350 C)	Hunter Green 6022* (PMS 342 C)	Autumn 2048* (PMS 404 C)	Loden 6081* (PMS Black 5 C)	Sand 1064 (PMS 4665 C)	Coir/Natural 1099* (PMS 467 C)
Natural Beige 1153* (PMS 7530 C)	Zinc 7006* (PMS 140 C)	Taupe 2345* (PMS 408 C)	Rosewood 7178* (PMS 7589 C)	Chocolate 7097* (PMS 7596 C)	Walnut 7068* (PMS 7519 C)
Teak 7185* (PMS 412 C)	Sterling 2344* (PMS 430 C)	Black Shadow 2343* (PMS Black 7 C)	Gris/Charoal 2098* (PMS Black 6 C)	Solid Black 2000 (PMS Black)	White 1000 (PMS White)

CHAMPION SUPER NOP NONWOVEN SHEET/ROLL GOODS | DIVISION 9 | ZONES 2 & 3

CHAMPION SUPER NOP

54 OZ NONWOVEN SHEET/ROLL GOOD

SUGGESTED USES

Office Environments, Runners, Conference Rooms, Lobbies, Libraries, Retail/Department Stores, Entryways, etc.

Manufacturing Process:	Non-woven/needlepunched
Surface Aspect:	Hobnail (berber) pattern
Fiber:	100% Solution-dyed UV stabilized ASOTA™ polypropylene
Backing:	Premium composite rubber
Pile Height (± 0.5mm):	0.25"
Total Height (± 7.5%):	0.47"
Pile Weight (± 7.5%):	54 oz/sy
Total Weight (± 7.5%):	78 oz/sy
Sheet/Roll Width (± 2%):	6′ 7" or 13′ 2"

LIMITED WARRANTY

Full Commercial Warranty 5 years

Summary of Warranty

Products must be professionally installed to validate the warranty.

van Gelder, Inc. warrants Champion Super Nop Sheet/Roll Goods against wear for a period of 5 years in a commercial application. This warranty applies only to material that is properly installed and maintained, while being used as intended and recommended. If the defect is covered by this warranty and is reported to van Gelder, Inc. within the warranty period, van Gelder, Inc. will supply new material of same or similar grade to repair or replace the defective material.

- **Wear**
  Defined as complete removal of wear layer, pattern and color due to wear from normal traffic and maintenance. If the wear occurs within 5 years from date of purchase, van Gelder, Inc. will provide replacement materials or repair, of only the effected area.
- **Manufacturing Defects**
  van Gelder, Inc. warrants Champion Super Nop materials are free from manufacturing defects and will replace defective floor covering and reasonable installation costs for a period of up to five [5] years from date of purchase. van Gelder, Inc. will not pay labor costs to repair or replace materials that defects were apparent before or at the time of installation.
- **Other Limitations**
  - This warranty is non-transferable
  - Manufacturing defect must be reported within 3 months from date of purchase.
  - This Warranty covers only properly installed & maintained floors
  - van Gelder, Inc. excluded and will not pay for any consequential or incidental expenses.
  - van Gelder, Inc. reserves the right of final judgment and may refuse claims in certain instances.

*For a copy of the full warranty please ask for a warranty sheet

PACKING & DIMENSIONS

Sheet/Roll Width (± 2%): 6′ 7" or 13′ 2"

TECHNICAL SPECIFICATIONS

Dimensional Stability (ASTM D7570-09):	Pass
Electrostatic Propensity (EN 1815):	>2kV
Electrical Resistivity (IBM / ICL):	Pass, for R.H. ≥40%
Sound Insulation (ISO 10140-1:2010):	≥21dB
Thermal Retention (ISO 11092):	0.15 m K/W Pass

COLOR FASTNESS

To Light (ISO 105 B02):	5
To Water (ISO 105 E01):	5
To Shampoo (ISO 105 C06):	4-5
To Rubbing (ISO 105 X12):	4 (Dry), 3-4 (Wet)

FLAMMABILITY RATING

Smoke Density (ASTM E662)	Pass
Surface Flammability (FF 1-70 / ASTM D2859)	Pass

LEED-NC MR Credit 4 | IEQ Credits 4.1, 4.3, 5

MAINTENANCE

Regular vacuuming (Weekly in low-traffic areas, and daily or twice daily in areas with higher traffic) with a motor-driven brush and beater bar can remove up to 80% of surface dirt, and is the easiest way to prolong the life of your carpet.

Regular vacuuming is key to maintaining your carpet, but eventually the carpet color dulls from dirt and grime stuck in the fibers. The dirt is then carried further into the building to form more soil reservoirs. Additionally, the oil content (15%) of the soil causes particles to stick to carpet fiber and resist vacuuming. To restore the carpet to its best condition, frequent light cleaning gives the best result and is often very cost effective.

**For more information, plus instructions for stain removal, consult vG's Resource Center at* www.vangelder-inc.com/resources

IMPORTANT NOTICE

Sample swatches have been cut from an overall design; decoration and shade may vary.

YOUR AUTHORIZED SALES REPRESENTATIVE:

SOLUTIONS FOR EVERY ENVIRONMENT
1+ 866 284 6287 | www.vangelder-inc.com

vGIS_CSNSHEET_012617

van Gelder, Inc.
www.vangelder-inc.com
+1 866 284 6287

vG™ incorporated

EXPERIENCE IT FOR YOURSELF
Talk with your sales representative or request samples at samples@vangelder-inc.com