



40
MIL

NATURES VIEW STYLE RUSTIQUE

6" X 36" LUXURY VINYL PLANKS
CLASSIC COLORS & STYLES

- **MADE FOR HIGH TRAFFIC**
durable 40mil wear layer construction
- **SCRATCH & SLIP RESISTANT**
no special cleaners, sealers or wax necessary
- **WEATHERED LOOK**
seven popular natural wood looks to choose from

Superior performance and classic style for the most demanding environments.

When it comes to luxury vinyl plank, not all are created equal. The thicker the wear layer, the more durable the product, making Natures View Style Rustique 6" x 36" 40-mil planks one of the most resilient luxury vinyl products on the market.

Available in a range of seven modern-classic looks, Natures View Style Rustique offers nearly endless design possibilities while adding performance and function to your next flooring project.

LET'S GET STARTED:

Contact your representative or email samples@vangelder-inc.com for samples and more information.



Sand NVR4155



Ash NVR4245



Buff NVR5961



Driftwood NVR5466



Dark Chestnut NVR5971



Weathered Barn NVR2166



Nantucket NVR6011



CERTIFIED BY
SCS Global Services

NATURES VIEW STYLE RUSTIQUE

6" X 36" LUXURY VINYL PLANKS



SUGGESTED USES

Beauty Salons, Conference Rooms, Corporate Lunchrooms, General Office, Hospitals, Libraries, Pharmacies, Retail/Department Stores, Resorts, Restaurants, Spas and Supermarkets

Overall Thickness	3.175mm 0.125"
Wear Layer Thickness	1.0mm 40mil
Plank Size	6" x 36"

LIMITED WARRANTY

Full Commercial Warranty 16 years

Summary of Warranty *For a copy of the full warranty please ask for a warranty sheet
Natures View planks must be professionally installed to validate the warranty.

van Gelder, Inc. warrants Natures View Style Rustique first quality planks against wear for a period of 16 years in a commercial application. This warranty applies only to material that is properly installed and maintained, while being used as intended and recommended. If the defect is covered by this warranty and is reported to van Gelder, Inc. within the Warranty period, van Gelder, Inc. will supply new material of same or similar grade to repair or replace the defective material.

- Wear**
Defined as complete removal of wear layer, pattern and color due to wear from normal traffic and maintenance. If the wear occurs within 16 years from date of purchase, van Gelder, Inc. will provide replacement materials or repair, of only the effected area.
- Manufacturing Defects**
van Gelder, Inc. warrants Style Rustique first quality plank materials are free from manufacturing defects and will replace defective floor covering and reasonable installation costs for a period of up to one [1] year from date of purchase. van Gelder, Inc. will not pay labor costs to repair or replace materials that defects were apparent before or at the time of installation.
- Other Limitations**
 - This warranty is non-transferable
 - Manufacturing defect must be reported within 3 months from date of purchase.
 - This Warranty covers only properly installed & maintained floors
 - van Gelder, Inc. excluded and will not pay for any consequential or incidental expenses.
 - van Gelder, Inc. reserves the right of final judgment and may refuse claims in certain instances.

PACKING & DIMENSIONS

Plank 6" x 36":	26 planks/carton
Sq. Ft. per carton:	39 sq. ft
Overall Thickness	3.175mm 0.125"
Wear Layer Thickness	1.0mm 40mil
Weight:	38.82 lbs./carton

TECHNICAL SPECS (ASTM 1700-99)

Stability (EN 986)	Pass
Abrasion Resistance (EN 660)	Excellent (<0.15g/1000 cycles)
Static Load (ASTM F970 - Modified)	2000 psi
Sound Insulation (DIN 52210)	4dB
Slip Resistance (ASTM D 2047)	Pass (0.61 - Exceeds ADA Standards)
Stain & Chemical Resistance (ASTM 925)	Excellent
Light Resistance (F 1515)	Pass
Indentation Resistance (F 1914)	Pass (<8%)

FLAMMABILITY RATING

Radiant Panel Test (ASTM E648)	Class 1
Smoke Density (ASTM E662)	Pass (<450 sdi)
Heat Stability (ASTM 1514)	Pass
HUD/FHA Requirements	Exceeds

INSTALLATION

Surface Preparation: Sub floor (wood or concrete) must be structurally sound, clean, smooth, dry free from dust, dirt, wax, grease, and/or any other foreign material that would interfere with a good bond. DO NOT USE adhesives where moisture is present in concrete or wood-type sub floors. Moisture may retard or prevent adhesive from setting.

Primer: Latex primer acts like a sealer but allows adhesion of the planks to the concrete floors. It also helps preventing moisture from getting between the planks and sub floor.

Tools required: Utility knife, carpenter square, chalk, string, pencil and rolling pin.

INSTALLATION GUIDE

Style Rustique planks and adhesive must be conditioned at room temperature, minimum 65°F for 24 hours before and 24 hours after installation. Spread adhesive with a 1/16" X 1/16" X 1/16" square-notch trowel. Apply adhesive to sub floor according to the instructions on the container. Spread adhesives to small areas to avoid letting the adhesive dry too much before you have finished laying your plank. For planks use the wet set installation instructions. Roll each section immediately upon completing with a 100 pound three-section roller. Re-roll the entire floor after one or two hours. If you do not have access to a roller, then use a rolling pin and your body weight. Do not wash or treat the floor for a minimum of 48 hours after installation.

MAINTENANCE

We recommend using a non-rising cleaner that leaves no film and suggest that you vacuum, sweep or dust mop twice per week. High-traffic areas might require more frequent cleaning.

Wipe up food and other spills immediately using recommended cleaner and a soft cloth. You should NEVER USE ABRASIVE CLEANERS, POWDERS, OIL CLEANERS, WAXES OR DISH DETERGENT. These will scratch the surface or leave a film.

When using a vacuum, if possible turn off the beater and use a hose or wand with an upholstery attachment. Vacuum wheel may also be a source for indenting and scuffing, check the wheels for embedded grit.

To remove scuff marks you can use a soft cloth to rub it out. If they difficult to remove try using a product named "Oops Painter Wipes". Rinse the area well afterwards with clean warm water and allow to dry. Please note that these procedures may help remove stains from vinyl floors, but cannot guarantee complete removal. Burns, holes or "permanent" stains may require a replacement "patch of that section of the floor.

To remove damaged planks you can use a hair dryer, which heats up the adhesive allowing the plank to be picked up. When the plank is up, use a wide blade putty knife and pull it out, then put the new plank down once the surface has been prepared. You should NEVER USE A HEAT GUN as this emits too much heat and will damage the planks.

IMPORTANT NOTICE

Sample swatches have been cut from an overall design, decoration & shade may vary. The random nature of wood and other natural materials from which our patterns are designed means that significant color and design variation is normal and enhances the look of the planks.

YOUR AUTHORIZED SALES REPRESENTATIVE:

vGIS_NVR636_000717



van Gelder, Inc.
www.vangelder-inc.com
+1 866 284 6287

EXPERIENCE IT FOR YOURSELF
Talk with your sales representative or request samples at samples@vangelder-inc.com