

TWO-N-ONE

HYBRID MAT ENTRY SYSTEM

- TRUE SCRAPER-WIPER Solid-back grid coupled with heavy carpet scraper
- ENDLESSLY CUSTOMIZABLE
 Up to 36 carpet colors for solid or custom logo designs
- HIGHLY VERSATILE
 Can be made as a loose mat or glued wall-to-wall
- HEEL & WHEELED-TRAFFIC FRIENDLY Including shopping trolleys
- MADE FOR MEDIUM TO HEAVY TRAFFIC

Edged Two-n-One Mat with Champion Super Nop Carpet in Gris/Charcoal 2098



A scrape-and-clean system with unrivaled flexibility.

Smart and versatile, vG's Two-n-One hybrid matting system combines the function of Frontrunner SB - a heel-and-wheel friendly grid entry system - with your choice of durable all-weather walk-off carpet* together in a single mat.

The distinctive, seamless look of Frontrunner SB's serrated grid scrapes and captures dirt and debris, while the walk-off carpet* wipes away what's left, including excess moisture. Easily moved and cleaned, Two-n-One Mat is built to withstand medium to high traffic. Choose from a wide selection of shapes, sizes and colors in single tone or custom logo designs in either edged mat or semi-permanent wall-to-wall applications.

Two-n-One's nearly limitless versatility with no matwell or installation required - simply unroll and go!

SOLUTIONS FOR EVERY ENVIRONMENT 1+ 866 284 6287 | www.vangelder-inc.com

AVAILABLE WALK-OFF CARPETING OPTIONS:

Made to your specifications using our proprietary assembly process, Two-n-One is available in a wide variety of shapes, styles and colors, including custom logo mats.

Talk with your representative for more details on these and other available vG products:

- CHAMPION SUPER NOP (featured)
- ATLAS
- EAGLE
- HERCULES
- WINDSOR

LET'S GET STARTED:

Contact your representative or email samples@vangelder-inc.com for samples and more information.

TWO-N-ONE

HYBRID GRID MATTING SYSTEM



SUGGESTED USES

Indoor entryways or other high-traffic areas with no matwell.

SPECIFICATIONS (using Champion Super Nop Carpet)

Overall Thickness	0.5"
Grid Thickness	0.375"
Total Carpet Height*	0.47"
Carpet Pile Height*	0.25"
Carpet Pile Weight*	54 oz/sy
Total Carpet Weight*	78 oz/sy
Backing (Grid)	Flexible DINP plasticized PVC
Backing (Champion Super Nop Carpet*)	Premium Composite Rubber
Edging Material	PVC

LIMITED WARRANTY

2 years - Ask for warranty sheet for details

TECHNICAL SPECIFICATIONS (using Champion Super Nop Carpet)

Grid Material Flexible DINP plasticized PVC (Ribbed Grid)
Carpet Fiber* 100% Solution-dyed, UV stabilized
ASOTATM polypropylene
(Non-woven hobnail (berber) pattern)

Dimensional Stability (ASTM D7570-09)* Pass Electrostatic Propensity (EN 1815)* >2kV Electrical Resistivity (IBM / ICL)* Pass, for R.H. ≥ 40% Sound Insulation (ISO 10140-1:2010)* \geq 21dB Thermal Retention (ISO 11092)* 0.15 m K/W Pass

COLOR FASTNESS (using Champion Super Nop Carpet)

To Light (ISO 105 B02)*	5
To Water (ISO 105 B01)*	5
To Shampoo (ISO 105 B06)*	4-5
To Rubbing (ISO 105 B02)*	Dry: 4 Wet: 3-4

FLAMMABILITY

Smoke Density (ASTM E662)	Passes
Surface Flammability (FF 1-70/ASTM D2859)	Passes

ENVIRONMENT

van Gelder, Inc. does not use any substances currently included in the SVHC (Substances of Very High Concern) list under REACH (Registration, Evaluation, Authorization and Restriction of CHemical substances) in any matting products. All PVC grid products are 100% recyclable.

LEED-NC: Version 3
IEQ Credit 4.1, 4.3, 5
MR Credit 4

MAINTENANCE

Daily: Vacuum with an industrial cleaner. Should stones, salt particles or other solid matter become embedded between the surface ribs, remove using a blunt instrument (screwdriver) or similar device. In addition to daily routine above, its important to remove chewing gum deposits and stains as they appear.

Weekly: Complete daily cleaning routine, then clean top surface using cylindrical brush machine. Initially work in direction of top ribs then across the ribs to complete cleaning. If a cylindrical brush machine is not available equally good results can be achieved using a high-pressure water extraction process.

For more information on Two-n-One installation or maintenance, contact your van Gelder, Inc. sales representative.

YOUR AUTHORIZED SALES REPRESENTATIVE:

