


FENWAY NOP


37 OZ. BERBER · INDOOR/OUTDOOR CARPET


Classic berber style, Fenway Nop performance is great for medium-traffic areas.


Suitable for medium to heavy traffic areas, Fenway Nop's heavy fiber and dense 37 oz. material prevents crushing while being easy to move or install. Fenway Nop's solution-dyed, UV stabilized ASOTA® polypropylene fiber and premium composite rubber backing make it resilient in extreme climate conditions, and easily cut into any shape without edge ravel.

- High-performance needlepunched construction
- Solution-dyed, UV stabilized ASOTA® polypropylene fiber
- Available in sheet/roll goods and custom/logo matting


01. Sterling FN05


02. Charcoal FN19


03. Steel Blue FN28


04. Sisal FN199


05. Zinc FN13


06. Walnut FN21

FENWAY NOP BERBER CUSTOM LOGO MATTING | DIVISION 9 | ZONES 1, 2 & 3

SOLUTIONS FOR EVERY ENVIRONMENT
1+ 866 284 6287 | www.vangelder-inc.com

FENWAY NOP

BERBER INDOOR/OUTDOOR CARPET

1·2·3 ZONES | INDOOR | OUTDOOR

SUGGESTED USES
Office Environments, Runners, Conference Rooms, Lobbies, Libraries, Retail/ Department Stores, Entryways, etc.


Manufacturing Process:	Non-woven/needlepunched
Surface Aspect:	Hobnail (berber) pattern
Fiber:	100% Solution-dyed UV stabilized ASOTA®polypropylene
Backing:	Premium composite rubber
Pile Height (± 0.5mm):	0.125"
Total Height (± 7.5%):	0.375"
Pile Weight (± 7.5%):	37 oz/sy
Total Weight (± 7.5%):	64 oz/sy
Sheet/Roll Width (± 2%):	6' 7" or 13' 2"

AVAILABLE SIZES

18" x 24"	3' x 5'	3' x 10'	4' x 8'	6' x 6'	6' x 12'	8' x 20'
2' x 3'	3' x 6'	3' x 12'	4' x 10'	6' x 8'	6' x 20'	12' x 12'
3' x 4'	3' x 8'	4' x 6'	4' x 12'	6' x 10'		

CUSTOM SIZES
Length: Up to 13'
Width: Up to 100' Long

EDGING
Low Profile
ADA Compliable



LIMITED WARRANTY
Full Commercial Warranty 5 years
Summary of Warranty
Products must be professionally installed to validate the warranty.
van Gelder, Inc. warrants Fenway Nop Sheet/Roll Goods against wear for a period of 5 years in a commercial application. This warranty applies only to material that is properly installed and maintained, while being used as intended and recommended. If the defect is covered by this warranty and is reported to van Gelder, Inc. within the Warranty period, van Gelder, Inc. will supply new material of same or similar grade to repair or replace the defective material.

- Wear
- Defined as complete removal of wear layer, pattern and color due to wear from normal traffic and maintenance. If the wear occurs within 5 years from date of purchase, van Gelder, Inc. will provide replacement materials or repair, of only the effected area.
- Manufacturing Defects
- van Gelder, Inc. warrants Fenway Nop materials are free from manufacturing defects and will replace defective floor covering and reasonable installation costs for a period of up to one [1] year from date of purchase. van Gelder, Inc. will not pay labor costs to repair or replace materials that defects were apparent before or at the time of installation.
- Other Limitations
  - This warranty is non-transferable.
  - Manufacturing defect must be reported within 3 months from date of purchase.
  - This Warranty covers only properly installed & maintained floors.
  - van Gelder, Inc. excluded and will not pay for any consequential or incidental expenses.
  - van Gelder, Inc. reserves the right of final judgment and may refuse claims in certain instances.

**For a copy of the full warranty please ask for a warranty sheet.*

EXPERIENCE IT FOR YOURSELF
Talk with your sales representative or request samples at samples@vangelder-inc.com

PACKING & DIMENSIONS

Sheet/Roll Width (± 2%):	6' 7" or 13' 2"

TECHNICAL SPECIFICATIONS

Dimensional Stability (ASTM D7570-09):	Pass
Electrostatic Propensity (EN 1815):	>2kV
Electrical Resistivity (IBM / ICL):	Pass, for R.H. ≥40%
Sound Insulation (ISO 10140-1:2010):	≥21dB
Thermal Retention (ISO 11092):	0.15 m K/W Pass
COLOR FASTNESS	
To Light (ISO 105 B02):	5
To Water (ISO 105 E01):	5
To Shampoo (ISO 105 C06):	4-5
To Rubbing (ISO 105 X12):	4 (Dry), 3-4 (Wet)

FLAMMABILITY RATING

Smoke Density (ASTM E662):	Pass
Surface Flammability (FF 1-70 / ASTM D2859):	Pass
LEED-NC	**MR CREDIT 4 | IEQ CREDITS 4.1, 4.3, 5**

MAINTENANCE
Regular vacuuming (Weekly in low-traffic areas, and daily or twice daily in areas with higher traffic) with a motor-driven brush and beater bar can remove up to 80% of surface dirt, and is the easiest way to prolong the life of your carpet.
Regular vacuuming is key to maintaining your carpet, but eventually the carpet color dulls from dirt and grime stuck in the fibers. The dirt is then carried further into the building to form more soil reservoirs. Additionally, the oil content (15%) of the soil causes particles to stick to carpet fiber and resist vacuuming. To restore the carpet to its best condition, frequent light cleaning gives the best result and is often very cost effective.
*For more information, plus instructions for stain removal, consult vG's Resource Center at www.vangelder-inc.com/resources

IMPORTANT NOTICE
Sample swatches have been cut from an overall design; decoration and shade may vary.

YOUR AUTHORIZED SALES REPRESENTATIVE:

vG_CLM_Fenway_101922

van Gelder, Inc.
www.vangelder-inc.com
+1 866 284 6287

vG incorporated

FENWAY NOP BERBER CUSTOM LOGO MATTING | DIVISION 9 | ZONES 1, 2 & 3