

Heron Rib Interlocking Grid Tile

vii2822

PRODUCT SPECIFICATIONS	STANDARD/NORMS	DATA
Composition		Flexible Polyvinyl Chloride (PVC)
Overall Thickness		13/32 in. 10.5mm
Roll Options		2', 3' or 4' widths 33' length
Weight		1.10 lbs/ sq.ft
Gauge (±10%)		13/32" (10.5mm)
Available Sizes		2' x 33' 3' x 33' 4' x 33'
PVC Certified Slip Resistance	ASTM F 1677	Dry: 0.9 Wet: 0.7
DIN 51097		Classification C
UV Light		Resistant to PVC degradation
FLAMMABILITY RATING		
Certified	EN 13501	CFL-SI
Composition		(EVA) Molded Ethylene Vinyl Acetate
Slip Resistance	DIN 51097	Classification C
Fire Resistant	DIN 4102	Classification B2
LEED-NC		
MR Credit 4	LEED-NC v3 For 1-2 points: \$ value of all	Black: 100% pre-consumer recycled content Gray: 32% pre-consumer recycled content
IEQ Credit 5	LEED-NC v3 For 1 point: Semi-permanently installed entrance system of at least 10" in length and maintained on a weekly basis	This product is a semi-permanent installation