




ELEMENTS 350 SERIES

RECYCLED RUBBER FLOORING


Elements 350 Series helps make your facility stand out amongst all others.

With the same durability and strength as the 100 Series and 200 Series, 350 series offers a burst of color that will make your facility stand out amongst all others.


- The highest quality rubber gym flooring available
- Our EPDM color granules are made from 30-100% post consumer
- Easy Maintenance




01. Salt and Pepper 526



02. Milky Way 503




03. Blue Bahia 523




04. Grass Green 522



05. Terrific Tan 505



06. Rouge 524



07. Fiesta Purple 525

ELEMENTS 350 SERIES

HEAVY DUTY ROLLED RUBBER FLOORING



SUGGESTED USES

Weight Rooms, Home Gyms, Fitness Centers, Health Clubs, Recreation Centers, Golf Shops and Golf Courses, Schools and Universities, Play Areas, Day Care Centers, Fire and Police Stations, Physical Therapy Centers, Ice skating facilities, ect.

Construction (ISO 2424):	SBR Rubber Black + 35% Color EPDM/Recycled Rubber
Density (ASTM D3676):	60 pcf - 80 pcf
Hardness (ASTM D2240 (Shore A):	60 ± 5
Tear Strength (ASTM D624):	70pli - 80 pli min.
Elongation (ASTM D412):	> 145% - 300%
Tensile Strength (ASTM D412):	200 psi - >220psi
Flexibility (ASTM F137 1/4" Mandrel):	Pass
Resistance to Chemicals (ASTM F825):	No Change
Force Reduction (ASTM F2772)	12.9% - 13.7%
Energy Restitution (ASTM F2772)	85% - 86%
Abrasion Resistance (ASTM D3389)	<1.7g. 1000 cycles
Static Load Limit (ASTM F970)	0.001' @ 250 PSI
Coefficient of Friction (ASTM D2047)	>0.95
Slip Resistance (ASTM F2772)	Pass
VOC Compliant (ASTM D6116 / CA 1350)	Yes
Rolling Load (EN1569)	Pass
Resistance to Impact (EN1517)	14 N/m
Resistance to Identification (EN1516)	0.1mm
Vertical Deformation (ASTM F2772)	1.4mm
Indoor Air Quality (CA Spec 01350):	Pass
Coefficient of Friction (ASTM D2047):	> 0.96

PACKAGING & DIMENSIONS

Size	Colors	Thickness
Roll Goods 4' wide x 95' long (Standard: 4' x 50' roll)	Grass Green 522, Blue Bahia 523, Milky Way 503, Rouge 524, Terrific Tan 505, Fiesta Purple 525, Salt and Pepper 526	9mm (3/8") Thick
Roll Goods 4' wide x 95' long (Standard: 4' x 50' roll)	Only Blue Bahia 523, Rouge 524, Salt & Pepper 526	12mm (1/2") Thick
Square Tile 23" x 23"	All Colors available	9mm (3/8") Thick @ 3.67 sq. ft. / Tile 500 sq. ft. minimum order (@137 tiles)
Interlocking Tile 23" x 23"	All Colors available	9mm (3/8") Thick @ 3.28 sq. ft. / Tile (@153 interlocking)

LEED-NC

MR Credit 4 | IEQ Credits 4.1, 5

MAINTENANCE

For maintenance visit www.vangelder-inc.com.

To prevent slip and fall accidents, ALWAYS use a "WET FLOOR" sign when wet rubber flooring has been cleaned and is open to floor traffic.

IMPORTANT NOTICE

Sample swatches have been cut from an overall design; decoration and shade may vary.

EXPERIENCE IT FOR YOURSELF

Talk with your sales representative or request samples at samples@vangelder-inc.com

LIMITED WARRANTY

Full Commercial Warranty

5 years

Summary of Warranty

Products must be professionally installed to validate the warranty.

van Gelder Inc. warrants Elements 350 Series Sheet/Roll Goods against wear for a period of 5 years in a commercial application. This warranty applies only to material that is properly installed and maintained, while being used as intended and recommended. If the defect is covered by this warranty and is reported to van Gelder Inc. within the warranty period,

van Gelder Inc. will supply new material of same or similar grade to repair or replace the defective material.

• Wear

Defined as complete removal of wear layer, pattern and color due to wear from normal traffic and maintenance. If the wear occurs within 5 years from date of purchase, van Gelder Inc. will provide replacement materials or repair, of only the effected area.

• Manufacturing Defects

van Gelder Inc. warrants Elements 350 Series materials are free from manufacturing defects and will replace defective floor covering and reasonable installation costs for a period of up to one [1] year from date of purchase. van Gelder Inc. will not pay labor costs to repair or replace materials that defects were apparent before or at the time of installation.

• Other Limitations

- This warranty is non-transferable.
- Manufacturing defect must be reported within 3 months from date of purchase.
- This warranty covers only properly installed & maintained floors.
- van Gelder Inc. excluded and will not pay for any consequential or incidental expenses.
- van Gelder Inc. reserves the right of final judgment and may refuse claims in certain instances.

***For a copy of the full warranty please ask for a warranty sheet.**

INITIAL CLEANING

Do not wash floor for at least 5 days after installation. An initial cleaning needs to be done to remove any dirt and grit from the job site and to prepare the floor prior to applying a sealer or finish. Failure to clean properly will cause finish bonding issues as well as the entrapment of dirt in the floor.

To avoid possible damage to the flooring, the following should never be used on the floor:

- Steel wool or abrasive brushes
- Abrasive or alkaline cleaners
- Solvents of any type

YOUR AUTHORIZED SALES REPRESENTATIVE:

VG_InfoSales_350Series_100523



van Gelder, Inc.
www.vangelder-inc.com
+1 866 284 6287