

# PRODUCT SPECIFICATIONS



## Frontrunner Grid Matting

vii2822

GRID SPECIFICATIONS	STANDARD/NORMS	DATA
Composition		Flexible PVC
Overall Thickness (Regular/LP)		0.563" (14mm) / 0.375" (10.5mm)
Roll Width		4' only
Roll Length		33' Standard
PRODUCT RATINGS		
Friction	ASTM C1028 DIN 51130	0.54 (Wet), 0.66 (Dry) R11, V10
Fire Resistance	ASTM E648	Class 1
Flame Retardant Grade	EN ISO 13501-1:2007-Cfl	S1
Abrasion	ASTM D3884	0.4%/1,000 cycles
UV Resistance	Uncolored PVC material	BS EN 607=Delta E 1.02
Acoustic		Excellent sound absorption properties
Thermal		Functional $\geq -23^{\circ}\text{C}$ , $\leq +60^{\circ}\text{C}$
LEED		
MR Credit 4	LEED-NC v3 For 1-2 points: \$ value of all	Black: 100% pre-consumer recycled content Gray: 32% pre-consumer recycled content
IEQ Credit 5	LEED-NC v3 For 1 point: Semi-permanently installed entrance system of at least 10' in length and maintained on a weekly basis	This product is a semi-permanent installation