





# FREESTAHYL

## PATTERNED SCROLL CARPET TILE


Themes of contemporary art, Freestahyl translates the geometric patterns found in abstract murals of urban artistic expression into a free-form canvas for the floor. The modern-spirited conceptual motif scrolls across 24"x24" tiles in 7 beautifully saturated neutral tones allowing design flexibility for a variety of creative and effortless installations.



**Bice**




**Blackstone**



**Riverstone**



**Adobe**



**Moleskin**



**Wren**



**Sloe**

SOLUTIONS FOR EVERY ENVIRONMENT  
1+ 706 602 4186 | [www.vangelder-inc.com](http://www.vangelder-inc.com)

# FREESTAHYL

## 15 OZ. PATTERNED SCROLL CARPET TILE



### SUGGESTED USES:

Lobbies, Libraries, Retail/Department Stores, Entryways and other high-traffic areas or spaces.

|                                   |   |
|-----------------------------------|---|
| Construction                      | Patterned Scroll                                    |
| Standard Backing                  | Nexus® Modular                                      |
| Dye Method                        | Solution Dyed                                       |
| Fiber Type                        | Encore® SD Ultima® (with recycled content)          |
| Face Weight                       | 15 oz./sy (509 grams/m <sup>2</sup> )               |
| Pile Density                      | 8852 oz./y <sup>3</sup> (328.24 kg/m <sup>3</sup> ) |
| Pattern Repeat                    | N/A   |
| Gauge                             | 1/12 (4.72 rows/cm)                                 |
| Stitches                          | 10.50 stitches/in (4.13 stitches/cm)                |
| Total Thickness (nominal average) | 0.217 inches  |
| Standard Size                     | 24" x 24" approx. (60.96cm x 60.96cm)               |
| Price Level:                      | \$\$  |
| Special Treatments                | ProTex® Soil Release                                |
| Optional Backings                 | Nexus® Cushion                                      |
| Standard Adhesive                 | Commercial on Premium Modular and LVT Adhesive      |
| Optional Adhesive                 | TileTabs  |

### LIMITED WARRANTY

Full Commercial Warranty 1 years  
Summary of Warranty

We extend certain warranties that cover products manufactured with Nexus® Modular backing. These warranties protect the original end use purchaser against performance deficiencies in specific categories. The length of time covered by each warranty listed below is for the useful life of the carpet, provided that the carpet is installed using the full spread modular adhesive or TileTabs® method and other guidelines described in our carpet installation instructions, and the carpet is maintained in accordance with our carpet maintenance instructions.

For carpet backed with Nexus Modular, the following lifetime warranties apply:

- Tuft Bind (edge ravel, yarn pulls, zippering): Under normal use carpet will not fail to perform due to insufficient tuft bind as evidenced by edge ravel, yarn pulls, or zippering.
- Delamination: Under normal use, carpet will not fail to perform due to the delamination of the secondary backing.
- Dimensional Stability: Under normal use and atmospheric conditions, Nexus Modular is dimensionally stable and will not shrink, grow, cup, or dome.

Should our Nexus Modular product fail to perform as warranted above, we will resolve the deficiency at our discretion by one or more of the following methods at no charge for materials, freight, and labor: repair the affected area replace the affected area with comparable product refund the full purchase price of the product in affected area. If carpet is to be replaced, areas must be cleared at the customer's expense of all equipment, furnishings, partitions, and similar materials that may have been placed over the carpet subsequent to completion of the original installation. In the event replacement is to be made for carpet that is not a current product manufactured by us, replacement will be made with a comparable style from the current product line.

*\*For a copy of the full warranty please ask for a warranty sheet.*

### PACKAGING & DIMENSIONS:

Tiles (24" x 24"): 18 tiles, 72 SF/Carton (41 lbs per carton)

### ENVIRONMENTAL SPECIFICATIONS & TESTS

|                        |                                      |
|------------------------|--------------------------------------|
| SCAS / NSF 140         | Gold Certified                       |
| Total Recycled Content | 48.75%                               |
| Flooring Radiant Panel | Class 1                              |
| Smoke Density          | Less than 450.0 flaming (ASTM E 662) |
| Static Test            | Less than 3.0 kv (AATCC-134)         |
| ADA Compliance         | Compliant For Accessible Routes      |
| Pill Test              | Yes                                  |
| Light fastness         | Yes                                  |

### LEED-NC

MR Credit 4 | IEQ Credits 4.1, 4.3, 5

### INSTALLATION (Tile)

Before laying tiles, it is recommended they are stored at room temperature 60°F-70°F (15°C-20°C). The tiles can be loose laid on flat, dry floors free from impurities such as oil, grease etc. Cracked floors should be filled, and uneven floors covered with hardboard. Dusty floors should be primed. Because of the high insulation value of these tiles it is not recommended they be laid when under-floor heating systems are in use. On very large installations, it is advisable to secure 1 in 5 rows with double-sided tape. Where tiles are to be used under caster chairs, tiles should be fully secured. The tiles may be laid by marking across in the center of the room and working outwards from this, the marker cross may be moved to facilitate these full tiles in doorways, etc. Tiles must be laid by turning alternate tiles 90 degrees to obtain a checker pattern. An arrow on the back of each tile indicates the pile direction. Only tiles with the same batch number should be laid together.

### MAINTENANCE

Regular vacuuming (Weekly in low-traffic areas, and daily or twice daily in areas with higher traffic) with a motor-driven brush and beater bar can remove up to 80% of surface dirt, and is the easiest way to prolong the life of your carpet.

Regular vacuuming is key to maintaining your carpet, but eventually the carpet color dulls from dirt and grime stuck in the fibers. The dirt is then carried further into the building to form more soil reservoirs. Additionally, the oil content (15%) of the soil causes particles to stick to carpet fiber and resist vacuuming. To restore the carpet to its best condition, frequent light cleaning gives the best result and is often very cost effective.

### IMPORTANT NOTICE

Sample swatches have been cut from an overall design; decoration and shade may vary.

### YOUR AUTHORIZED SALES REPRESENTATIVE:

vg\_Infosales\_Freestahyl\_042823



van Gelder, Inc.  
www.vangelder-inc.com  
+1 706 602 4186

### EXPERIENCE IT FOR YOURSELF

Talk with your sales representative or request samples at [samples@vangelder-inc.com](mailto:samples@vangelder-inc.com)